

CRETE COLORS INTERNATIONAL, LLC

MATERIAL SAFETY DATA SHEET

I PRODUCT IDENTIFICATION

MANUFACTURER/SUPPLIER Crete Colors International, LLC
PO Box 93542
Phoenix, AZ 85070

FOR CHEMICAL EMERGENCY
Spill, Leak, Fire Exposure or Accident
CALL INFOTRAC – Day or Night: 800/535-5053
Outside the United States Call Collect: 352/323-3500

PRODUCT TRADE NAME: C² Tint™

II HAZARDOUS INGREDIENTS

CHEMICAL NAME	(COMMON NAME)	CAS NO.	NFPA CODE	ACGIH TLV/TWA	OSHA PEL/TWA
Sodium dioctyl sulfosuccinate	NA	577-11-7	1,0,0,-	NE	NE
Diethylene glycol monobutyl ether	NA	112-34-5	2,0,0,-	NE	NE
Organic chrome complex	NA	Proprietary	ND	ND	ND
Organic chrome complex	NA	Proprietary	ND	ND	ND
Organic chrome complex	NA	Proprietary	ND	ND	ND

III TYPICAL PHYSICAL DATA

	BOILING POINT (°F)	VAPOR PRESSURE (mm Hg)	VAPOR DENSITY (Air = 1)	EVAPORATION RATE (Butyl Acetate = 1)
Sodium dioctyl sulfosuccinate	78°C (173°F)	NA	NA	NA
Diethylene glycol monobutyl ether	230°C (466°F)	0.03 mmHg@ 20°C	NA	0.01
Organic chrome complex	NA	NA	>1	NA
Organic chrome complex	NA	NA	>1	NA
Organic chrome complex	NA	NA	>1	NA
	SPECIFIC GRAVITY		SOLUBILITY IN WATER	APPEARANCE AND ODOR
C ² Tint™	0.90-1.10		Soluble	liquid, slight odor

IV FIRE AND EXPLOSION HAZARD DATA

EMERGENCY OVERVIEW

C² Tint™ is a liquid with a slight odor and comes in various colors. Causes eye and skin irritation.

FLASH POINT (METHOD): >200°F (ASTM 3278)

FLAMMABLE LIMITS: Not determined.

EXTINGUISHING MEDIA: Carbon Dioxide, dry powder, and/or chemical foam.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus to protect against toxic and irritating fumes and smoke inhalation.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No known unusual hazards in a fire/explosion situation.

V HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Eyes, skin, ingestion, and inhalation.

CARCINOGEN INFORMATION: Not listed (OSHA, IARC, NTP).

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: No medical conditions affected by overexposure.

EFFECTS OF OVEREXPOSURE: Prolonged inhalation of vapor or mist may cause brain, lung and other organ damage.

EYE CONTACT: May cause severe eye irritation. May cause slight corneal injury

SKIN CONTACT: Prolonged contact may cause slight skin irritation

INHALATION: Mild irritant. Effects are temporary and reversible. Vapor and mist can cause headache, nausea, and irritation of nose, throat, and lungs. Use in well-ventilated area and avoid breathing vapors.

INGESTION: Ingestion may cause nausea, vomiting, diarrhea and gastrointestinal irritation. Consult a physician

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Flush with water for at least 20 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

SKIN CONTACT: Wash area with soap and water. Get medical attention if irritation develops or persists.

INHALATION: If breathing is difficult, remove person to fresh air and give artificial respiration. Call a physician or transport to a medical facility if cough or other symptoms develop.

INGESTION: DO NOT INDUCE VOMITING. Immediately give 2 glasses of water. Contact a physician.

VI REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: Protect from freezing.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing materials. Materials that reaction with water. Avoid strong acids and alkalines

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Hazardous polymerization will not occur.

VII SPILL OR LEAK PROCEDURES

SPILL, LEAK, WASTE DISPOSAL PROCEDURES: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Cover with absorbent material. Collect spilled material.

WASTE DISPOSAL METHODS: Do not dump into any sewers, on the ground, or into any body of water. This product is not classified as a hazardous waste under USEPA regulations. However, regulations do prohibit disposal of any liquid waste in a sanitary landfill. Solidification/stabilization may render the product suitable for disposal in a sanitary landfill. Dispose of in a manner approved for this material or in an approved hazardous waste facility. Consult appropriate federal, state, and local regulatory agencies to ascertain proper disposal procedures. Completely drain container before disposing in a sanitary landfill. Do not attempt to clean with water.

VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Under normal use conditions, with adequate ventilation, no special respiratory protective equipment is required.

VENTILATION: Provide adequate ventilation when using inside.

PROTECTIVE CLOTHING: Wear protective clothing such as long sleeved work shirt and pants, work boots, and rubber gloves as needed to avoid prolonged skin contact. Do not allow clothing to become saturated with product. If work practices cannot be adjusted to avoid excess clothing saturation, splash resistant or Tyvek clothing and boots may be required.

PROTECTIVE GLOVES: Nitrile rubber, neoprene rubber, natural rubber, or PVC.

EYE PROTECTION: Safety glasses with side shields are recommended. Splash resistant goggles or a face shield should be used prevent eye contact where wind-drift and excess atomization can pose a risk.

OTHER PROTECTIVE EQUIPMENT: Access to an eyewash is recommended. Provide clean water for washing skin. Personal protective clothing and use of equipment must be in accordance with 29 CFR 1910.133 and 29 CFR 1910.132.

IX SPECIAL PRECAUTIONS

WORK PRACTICES: Proper work practices and planning should be utilized to avoid contact with workers and passersby. Avoid atomizing during application. Beware of wind drift. See the Product Data sheet and label for specific precautions to be taken during use. Smoking, eating and drinking should be discouraged during the use of this, or any, chemical product. Wash hands before breaks and at the end of a shift.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Wear appropriate safety equipment and clothing. Avoid contact with eyes, skin, and clothing. Do not touch face with hands or gloves that may be contaminated with this product. Do not take internally. Avoid breathing mist.

Store in a cool, dry, well-ventilated place. Keep containers tightly closed when not dispensing product. Treat empty containers as if they were full.

OTHER PRECAUTIONS: Avoid contact with eyes and skin. Do not take internally. Wash thoroughly after handling. Do not eat, drink, or smoke in work areas.

X REGULATORY INFORMATION

SHIPPING:

NATIONAL MOTOR FREIGHT CLASSIFICATION:

SARA 313 REPORTABLE:

CHEMICAL NAME	CAS	UPPERBOUND CONCENTRATION % BY WEIGHT
Diethylene glycol monobutyl ether	112-34-5	90%

CALIFORNIA PROPOSITION 65:

This product contains chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

XI OTHER

MSDS Status: **Date of Revision:** June 18, 2009
For Product Manufactured After: June 1, 2009
Changes: Test product.
Item #:
Approved By: Regulatory Department

DISCLAIMER:

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. **Crete Colors International, LLC expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described.** This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

DATE OF PREPARATION: June 18, 2009